



**SHOTCRETE
SLAB POURS
POOL BUILDING
PEA-ROCK
CONCRETE REPAIR
RETAINING WALLS
GROUTING**

- » Heavy-Duty Design
- » High Pressure and Production Rate
- » Perfect for Shotcrete and Slabs
- » Pumps 3/8" Pea Rock and 3/4" Material
- » Optional Air Vibrator
- » Remix Agitator (standard on model 636)



	Model 536	Model 636
Max. Output	36 cu yd/hr (28 m ³ /hr)	50 cu yd/hr (38 m ³ /hr)
Pressure	900 psi (62 bar)	800 psi (55 bar)
Max Aggregate Size	3/4" minus (25 mm)	3/4" minus (25 mm)
Concrete Cylinder Diameter	5" (127 mm)	6" (152 mm)
Concrete Cylinder Stroke	36" (914 mm)	36" (914 mm)
Full Flow S-Tube	5" (127 mm)	6" (152 mm)
Discharge Outlet Size	5" (127 mm)	5" (127 mm)
Power Source	Diesel 60 hp	Diesel 80 hp
Length	162"	162"
Width	70"	70"
Weight	4,000 lb (1,814kg)	4,300 lb (1,950kg)
Tires	15"	15"
Axle	Single	Single



Maximum output and pressure cannot be reached simultaneously. Performance will vary depending on power unit, hydraulic pressure, cycle rate, mix design and placement line.

Northeast

4141 Airport Road
Cincinnati, OH 45226
Phone: 513.321.2950
Fax: 513.321.8178
Toll-Free: 1.888.349.2950

Southeast

9202 Meadow Vista Blvd.
Houston, TX 77064
Phone: 281.469.7102
Fax: 281.469.9524
Toll Free: 1.866.469.7102

West

1726 South Magnolia Ave.
Monrovia, CA 91016
Phone: 626.256.9310
Fax: 626.359.7985
Toll Free: 1.888.393.8635