

PLASTER / STUCCO PUMP

www.airplaco.com



**Plaster, Stucco, EIFS, Fireproofing,
Coatings, Finishing, Splatter, Drywall**



The AIRPLACO MINI includes a complete hose and nozzle package including 1 inch polegun nozzle, material hose, air hose, pressure gauge and couplings.



SprayMaster *Mini*

| | |
|------------------------|-------------------------------|
| Max. Output | 0-2 gal / min (7.5L) |
| Material Line Pressure | 0 to 200 psi (13.8 bar) |
| Pumping Distance | 150 ft (46m) |
| Material Hopper | 15 gal (2 cu ft) (57L) |
| Rotor / Stator | 2L3 |
| Outlet Size | 2 in |
| Max. Aggregate Size | .125 in (3mm) |
| Power | 1 HP electric 110 Volt 15A |
| Overall Dimensions | 26 in W x 54 in L x 41 in H |
| Hopper Height | 32 in (81cm) |
| Weight | 190 lb (86 kg) |
| Controls | Manual / Remote |

Maximum output and pressure cannot be reached simultaneously. Performance will vary depending on power unit, hydraulic pressure, cycle rate, mix design and placement line.



Up to 2,000 square feet per hour
applying an 1/8" thick coating
Pumps up to 150 ft

AIRPLACO
EQUIPMENT COMPANY
Since 1946

TRIED-AND-TRUE, BUILT TO PERFORM