

# SprayMaster



Model SM-78E

**Stucco, Plaster, Fireproofing, EIFS, Acoustical, Cementitious coatings**



- \* Powerful rotor / stator design
- \* Large 60 gallon hopper
- \* Two bags fireproofing or three-bag stucco mix
- \* 20-30 bags / hour of fireproofing
- \* 1500-2000 sq ft / hr of 1/2 in thick stucco
- \* Pumping distances up to 200 ft
- \* Easy movement over rough terrain
- \* Variable speed
- \* Low hopper height for easy filling
- \* Remote with speed control / 125 ft cord
- \* 15 in OD rear wheels / 10 in OD front casters
- \* Forward and reverse flow control
- \* Fits through 36 in wide doorway
- \* Runs on 10,000 W or greater generator
- \* Optional air compressor

## SPECIFICATIONS

Max. Production Capacity	0-10 gal / minute
Material Line Pressure	0 to 500 psi
Air Output	12 cfm @ 90 psi
Material Hopper	60 gal
Rotor / Stator	2L6
Outlet Size	2 in
Max. Aggregate Size	.125 in (3mm)
Power	5 HP variable 208/240 V 30A 1 or 3 Phase
Overall Dimensions	33 in W x 72 in L x 43 in H
Hopper Height	32 in
Approx. Weight	585 lb
Controls	Manual / Remote

Performance is relative to cycle rate, mix characteristics, line size and distance. Max output, line pressure and distance cannot be achieved simultaneously. Specifications are subject to change.

AP-SM78E-09

### Northeast

4141 Airport Rd.  
Cincinnati, OH 45226-1692  
513.321.2950  
888.349.2950  
ohsales@airplaco.com

### West

1726 South Magnolia Ave.  
Monrovia, CA 91016-4595  
626.256.9310  
888.393.8635  
casales@airplaco.com

### Southeast

9202 Meadow Vista Blvd.  
Houston, TX 77064-2012  
281.469.7102  
866.469.7102  
txsales@airplaco.com