

Quality through Experience.

AIRPLACOTM

www.airplaco.com

Concrete & Grouting Pumps
Gunitite & Shotcrete Equipment
Plastering & Fireproofing Equipment

Division of Mesa Industries, Inc.

the Handy-GroutTM

Hand-operated portable grout pump

When the job is too small to justify sending out an engine-powered grouting rig, or the grout site is hard to reach with full-size equipment, just carry in the HANDY-GROUT and start pumping.

A pressure grouting original, the Handy-Grout is a hand-operated, self-priming, positive piston pump. It is designed to pump a wide variety of high viscosity slurries and grouts.

Specifications

Production Capacity: 15 cu. ft./hr. (112 gallons)
Line Pressure: 0 - 100 psi plus
Material Hopper: 5 gal (19L)
Shipping Weight: 53 pounds
Dimensions: 24"L x 16"W x 26"H

Applications

Machine base grouting, mud-jacking, door bucks, void filling, piling encasements, underlaying/topping, post tensioning, rock/soil anchors, precast tunnel joints, waterproofing, pipe jacking slurry, tunnel liners, pre-cast tilt-up panels, T-joints, concrete planks, traffic dividers, mining applications and more!



Handy-Grout Features

- * Lightweight design
- * Polyurethane hopper
- * Cast assembly
- * In-line discharge pressure gauge
- * Self-priming horizontal manifold
- * Hose assembly - 1" x 10'
- * Straight pipe nozzle

Find us on the Web! www.airplaco.com

Available at any of our three convenient locations!

Northeast
4141 Airport Rd.
Cincinnati, OH 45226-1692
513.321.2950
888.349.2950
ohsales@airplaco.com

West
1726 South Magnolia Ave.
Monrovia, CA 91016-4595
626.256.9310
888.393.8635
casales@airplaco.com

Southeast
9202 Meadow Vista Blvd.
Houston, TX 77064-2012
281.469.7102
866.469.7102
txsales@airplaco.com

Performance is relative to cycle rate mix characteristics, line size and distance. Max output, line pressure and distance can not be achieved simultaneously. We reserve the right to amend these specifications at any time.